



DRAIN WIRE TO N.O. CONTACT ON CIRCUIT BOARD:
PUMP ON HIGH LEVEL, DRAIN TANK

FILL WIRE TO N.C. CONTACT ON CIRCUIT BOARD:
PUMP ON LOW LEVEL, FILL TANK

Liquid Level Control Relay for pump up or pump down applications
UL File #E61377

Output: Isolated relay contacts, S.P.D.T. (1 Form C)
 Rating: 10 amp. resistive at 24, 120 VAC; 5 amp. resistive at 240 VAC
 Life: Mechanical - 5,000,000 cycles
 Electrical - 100,000 minimum at full load
 Input Voltage: 24, 120, 240 VAC, ± 10%
 Power Consumption: 3.0 VA max.
 Frequency: 50/60 Hz

Protection Isolation: 1500 VAC between probe and other terminals
 Mechanical Termination: 1/4" x .032" male fast-ons
 Mounting: 4 -.141" Dia. Mounting Holes
 Environmental Operating Temperature: -20°C to 55°C

PART#'S
 R-DLC-120 - 120VAC
 R-DLC-230 - 230VAC
 R-DLC-24 - 24VAC

PLEASE NOTE:
 THIS DRAWING AND SPECIFICATION IS THE PROPERTY
 OF INNOVATIVE COMPONENTS AND IS TO BE USED
 SOLELY AS A TECHNICAL REFERENCE BY INNOVATIVE
 COMPONENTS' CUSTOMERS. ANY REPRODUCTION OR
 DISTRIBUTION TO THE CONTRARY IS PROHIBITED.

SIGNATURE OF APPROVAL DATE
 PRINT: _____
 SIGN: _____

INNOVATIVE COMPONENTS
 384 OLD TURNPIKE ROAD, P.O. BOX 294
 SOUTHTONINGTON, CT. 06489

STANDARD TOLERANCES .000 = ± .010 .00 = ± .050 .0 = ± .100 0 = ± .200 ANGLES ± 5° TEMP ± 5°C	TITLE: DUAL LEVEL CONTROL RELAY	
	MODEL: R-DLC-xxx	DRAWN BY: F.J.K
	STOCK: X	DATE: 05/21/01
	FILENAME: C:\NCK7\PRTR\RELAY	SCALE: NONE
		REV: _____