



DRAIN WIRE TO S.L. CONTACT OR CORRECT BOARD-
PUMP OR BLOW OFF, DRAIN TANK

FILL WIRE TO S.L. CONTACT OR CORRECT BOARD-
PUMP OR LOW LEVEL, FILL TANK

Liquid Level Control Relay for pump up or pump down applications
UL File #881237

Output: Isolated relay contacts, S.P.D.T. (1 Form C)
Rating: 10 amp, resistive at 28, 120 VAC; 5 amp, resistive at 240 VAC
Life: Mechanical - 5,000,000 cycles
Electrical - 100,000 minimum at full load
Input Voltage: 24, 120, 240 VAC, ± 10%
Power Consumption: 3.0 W max.
Frequency: 50/60 Hz

Protection Isolation: 1500 VAC between probe and other terminals
Mechanical Termination: 1/8" x .003" male fast-on
Mounting: 4 - .141" Dia. Mounting Holes
Environmental Operating Temperature: -20°C to 50°C

9182-1
9182-10 - 10amp
9182-15 - 15amp
9182-20 - 20amp

11-00-00
INNOVATIVE COMPONENTS, INC.
11000 WILSON AVENUE, SUITE 100
DALLAS, TEXAS 75243-1100
PHONE: (214) 343-1100
FAX: (214) 343-1101

ORDER # _____ DATE _____
NAME _____
ADDRESS _____

INNOVATIVE COMPONENTS
400 GULF SHORE ROAD
PLANTERSVILLE, SC 29655

ORDER NUMBER QUANTITY DATE	PART # 9182-10 LIQ. LEVEL CONTROL RELAY	QTY 1
	PART # 9182-10	QTY 1
	PART #	QTY
	PART #	QTY