

DRAIN WIRE TO N.O. CONTACT ON CIRCUIT BOARD:
PUMP ON HIGH LEVEL, DRAIN TANK

FILL WIRE TO N.C. CONTACT ON CIRCUIT BOARD:
PUMP ON LOW LEVEL, FILL TANK

Liquid Level Control Relay for pump up or pump down applications
UL File #E61377


Output: Isolated relay contacts, S.P.D.T. (1 Form C)
Rating: 10 amp. resistive at 24, 120 VAC; 5 amp. resistive at 240 VAC
Life: Mechanical - 5,000,000 cycles
Electrical - 100,000 minimum at full load
Input Voltage: 24, 120, 240 VAC, $\pm 10\%$
Power Consumption: 3.0 VA max.
Frequency: 50/60 Hz

Protection Isolation: 1500 VAC between probe and other terminals
Mechanical Termination: 1/4" x .032" male fast-ons
Mounting: 4 -.141" Dia. Mounting Holes
Environmental Operating Temperature: -20°C to 55°C

PART#'S
R-DLC-120 - 120VAC
R-DLC-230 - 230VAC
R-DLC-24 - 24VAC

PLEASE NOTE:
THIS DRAWING AND SPECIFICATION IS THE PROPERTY
OF INNOVATIVE COMPONENTS AND IS TO BE USED
SOLEY AS A TECHNICAL REFERENCE BY INNOVATIVE
COMPONENTS' CUSTOMERS. ANY REPRODUCTION OR
DISTRIBUTION TO THE CONTRARY IS PROHIBITED.

SIGNATURE OF APPROVAL DATE
PRINT: _____
SIGN: _____



INNOVATIVE COMPONENTS

635 OLD TURNPIKE ROAD
PLANTSVILLE, CT. 06479

STANDARD TOLERANCES .000 = $\pm .010$.00 = $\pm .050$.0 = $\pm .100$ 0 = $\pm .200$ ANGLES $\pm 5^\circ$ TEMP $\pm 5^\circ\text{C}$	TITLE: DUAL LEVEL CONTROL RELAY MODEL: R-DLC-xxx STOCK: X FILENAME: C:\CK7\PRTR\RELAY	DRAWN BY: F.J.K DATE: 05/21/01 SHEET: 1 OF 1 SCALE: NONE REV:
--	--	---